

2 megapixel  
Long range network camera

---



**T2200A/B** / ~~205~~



#### KEY FEATURES

- Long range lenses 20-2200mm.
- 2 megapixel ultra low lux CMOS sensors
- Zoom / Auto-iris lenses
- H.264/MJPEG video compression
- Continuous zoom extender
- Hardware Wide Dynamic Range
- Multiple streams
- Real day & night, auto switch ICR filter
- EIS Video stabilization, optional in B models
- 3DNR Noise reduction
- Optical Defog lens
- Onvif complian
- IP68 waterproof

## Specifications:

	Model	THAL2200A	THAL2200B
Camera	Sensor	High sensitivity 1/1,8" CMOS	Ultra high sensitivity 1/2,3" CMOS
	Min. illumination	0,1Lux F1.4 / BW 0,01 F1.4	0,005 Lux F1.4
	Day/night	Automatic	
	WDR	100db. hardware	120dB. hardware
	Lens	20-2200mm.	20-2200mm.
	e-extender	40-4400mm.	40-4400mm.
	Zoom	110X	110X
	FOV Narrow	0,18° (0,09°)	0,23° (0,115°)
	FOV Wide	20,4° (10,2°)	24,8° (12,4°)
	Type	Autofocus, manual focus (remote), zoom	
Video	Max. resolution	2 megapixel 1920x1080 pixel	
	Max. frame rate	60 (WDR cancelled)	30
	EIS	Yes	Optional
	Compression	H.264, MJPEG	
	Streams	Multiple	
	Signal noise	>50dB.	
	Analogue/digital	Both	
Digital zoom	16x		
Network	Ethernet	1x 10/100 RJ45 Ethernet	
	Protocols	IPv4, RTSP, TFTP, HTTP, RTP, TCP, UDP	
System	Compatibility	Onvif	
	RS485	Yes	
	Defogging	Optical	
General	Working temp.	-32/55°C.	
	Waterproof	IP68 according to MIL-810	
	Heater/Fan	Yes	
	Humidity	95% RH	
	Power	28vDC. (18-32vDC.)	
	Consumption	35W., 120W with heaters on	
	Size (Cm.)	78x24x20	
	Weight	16,5Kg.	
Warranty	1 year		

\* Tanz Security reserves the right to change products or specifications without notice.



Tanz Security, Spain  
Gran Vía 19-21 2 planta  
48001 Bilbao, Spain

Tanz Security, Taiwan  
9F., No. 1095 Yucheng Road  
Gushan Dist., Kaohsiung  
80458 Taiwan

www.tanzsecurity.com  
info@tanzsecurity.com  
Tel: +886 905 186 990 (Support)  
Skype: tanz-support